



NOTE
 NE 4 was set by single proportioning (based on original distances) along the township line between N 1/4 4 & NE 3.
 SE 4 was set by double proportioning between NE 4 & W 1/4 10, and SW 4 & N 1/4 10.
 The C 1/4 9 was used as found according to a tie sheet by Dale Hagen on record with the County Surveyor.
 Distances matched Williams' 1871 map at C 1/4—E 1/4 and C 1/4—S 1/4, but the rest of the distances from Williams' map do not match good at all, so the distance and angle to N 1/4 9 from the map was not used.
 The N 1/4 9 area has been extensively searched with no evidence found. See corner tie sheet for more information.
 Green's Certified Survey Maps do not coincide with the "40" descriptions as surveyed according to "Bureau of Land Management Surveying Instructions 1973". There are overlap areas on state owned land as shown.
 Bearings as shown for bearing trees are magnetic (1/2° E. decl.).



I, M. E. Seymour RLS-1412 certify this is a correct representation of part of Sec. 9, T16N, R5E, to the best of my knowledge and belief.

M. E. Seymour 8-20-80

- LEGEND**
- Monuments found in place
 - Harrison Cast Iron
 - from Green's C.S.M.'s 989 & 990 (v. 4, pgs. 345-350)
 - Monuments set
 - Harrison Cast Iron
 - 1/2" iron pipe

T16N, R5E, Adams Co.
 Section 9; NE 1/4

Survey for the State of Wisconsin
 Department of Natural Resources

Scale 1" = 100' Dr. by MES 9/20/80

POSCA 1605 11001
 9,16-5