

CERTIFICATE OF SURVEY.

STATE OF WISCONSIN, } ss. J. M. Le. Smith Surveyor, in and for the County and State aforesaid, do
ADAMS COUNTY. hereby certify that I have surveyed and subdivided Section 24 Township 16 North of Range 7 East of 4th Principal Meridian, as represented by the courses and distances on the following plat, and annexed field-notes of survey:

- Established the center of the section at the point of intersection of straight quarter lines.
- Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.
- Established all lost corners at proportionate distances between known corners, according to original field-notes of the Government survey:



Plat of Section 24, Township 16 North, Range 7 East of 4th Principal Meridian. Scale, 80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian _____ East.
Surveyed and subdivided this 16 day of April A. D. 1905, in accordance with the State Laws and Instructions of the Commissioner of the General Land Office, and recorded on pages _____ of Register in the County Surveyor's office.
WITNESS my hand this 16 day of April A. D. 1905.

J. M. Le. Smith Surveyor.

The above work was done for Mr Henke "on county line"

MIS 2416070001

Jared Henke
Otto Henke

Requiring
on county line
79 chains &
set good st
Post on corner
made 2 new
at the corner
slightly displ

No.	DESCRIPTION
1	N. W. 1/4
2	N. E. 1/4
3	S. E. 1/4
4	S. W. 1/4
5	N. 1/4 Sec
6	E. 1/4 Sec
7	S. 1/4 Sec
8	W. 1/4 Sec
No.	SUBDIVISION
1	Center
2	North
3	East
4	South
5	West
6	Center
7	North
8	East
9	South
10	Center
11	East
12	South
13	West
14	Center
15	South
16	West
17	Center

DESCRIPTION of Section, Quarter Section and Quarter quarter Section Corners of Section
 _____ Township _____ North, Range _____ East of _____ Principal Meridian.

N. B. - The variation of needle adopted in establishing corners is _____

Government Corners.		Bearing Trees.	In. dia.	Courses they bear.	Links Distant.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.
No.									
1	N. W. Sec. cor. Identified								
2	N. E. Sec. cor. Identified	new	Blk oak	10 S-44-1/2-W	80	Blk oak	8	N-35-W	58 1/2
3	S. E. Sec. cor. Identified								
4	S. W. Sec. cor. Identified								
5	N. 1/4 Sec. cor. Identified								
6	E. 1/4 Sec. cor. Identified								
7	S. 1/4 Sec. cor. Identified	new	Blk oak	16 N-23-1/2-E	57				
8	W. 1/4 Sec. cor. Identified								
No. SUBDIVISION CORNERS.									
1	Center 1/4 Sec. cor.								
2	North 1/4-1/4s N. W. qr.								
3	East 1/4-1/4s N. W. qr.								
4	South 1/4-1/4s N. W. qr.								
5	West 1/4-1/4s N. W. qr.								
6	Center 1/4-1/4s N. W. qr.								
7	North 1/4-1/4s N. E. qr.								
8	East 1/4-1/4s N. E. qr.								
9	South 1/4-1/4s N. E. qr.								
10	Center 1/4-1/4s N. E. qr.								
11	East 1/4-1/4s S. E. qr.								
12	South 1/4-1/4s S. E. qr.								
13	West 1/4-1/4s S. E. qr.								
14	Center 1/4-1/4s S. E. qr.								
15	South 1/4-1/4s S. W. qr.								
16	West 1/4-1/4s S. W. qr.								
17	Center 1/4-1/4s S. W. qr.								

NAME OF SWORN ASSISTANTS.

CHAINMEN.	FLAGMEN.	AXMEN.
Fred Wenke Otto Wenke		

MINUTES.

Beginning at the identified North East corner of section 24 down 16-R-7-E on county line and ran south on section line on East side of 24 at 4 1/2-D-V 79 chains & 81 links to the established south East corner of said section set good stone. Then ran west at 5-D-V. 40 chains & 13 1/2 links to the Quarter Post on south side of 24. Found old Post and made 2 new bearings also made 2 new bearings at the North East corner of the section also set a big stone at the Quarter Post on East side of section. This work settled a long and ugly dispute

M1524160700001

W. G. Smith, Co. Surveyor