

# CERTIFICATE OF SURVEY.

STATE OF WISCONSIN, } ss. Wm L Smith Surveyor, in and for the County and State aforesaid, do  
ADAMS COUNTY. hereby certify that I have surveyed and subdivided Section 24 Township 16 North of Range 7 East of 4th  
Principal Meridian, as represented by the courses and distances on the following plat, and annexed field-notes of survey:  
Established the center of the section at the point of intersection of straight quarter lines.  
Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.  
Established all lost corners at proportionate distances between known corners, according to original field-notes of the Government survey.



Plat of Section 24 Township 16 North, Range 7 East of 4th Principal Meridian. Scale, 80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian \_\_\_\_\_ East.  
Surveyed and subdivided June 18 A. D. 1910, in accordance with the State Laws and Instructions of

the Commissioner of the General Land Office, and recorded on pages \_\_\_\_\_ of Register in the County Surveyor's office.  
WITNESS my hand this 18 day of June A. D. 1910.

Wm L Smith Surveyor.

The above work was done at the request of and for the Town Board of the town of Newbarkton D McLaughlin, L Johnson at A McKinnon Board

Adams County Field Notes Vol 5-Pg 16  
set line of stakes 2 rods west of center of highway for fence line

MIS24160700002

DESCRIPTION of Section, Quarter Section and Quarter quarter Section Corners of Section

Township North, Range East of Principal Meridian.

N. B. The variation of needle adopted in establishing corners is

No.	Government Corners.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.
1	N. W. Sec. cor. Identified								
2	N. E. Sec. cor. Identified	<i>new</i>	Blk oak	<i>These Bearings were made by one of April 16-1888</i>	10	S 44° W	80	Blk oak	8 N 35° W 5-2 1/2
3	S. E. Sec. cor. Identified								
4	S. W. Sec. cor. Identified								
5	N. 1/4 Sec. cor. Identified								
6	E. 1/4 Sec. cor. Identified								
7	S. 1/4 Sec. cor. Identified	<i>made 16-1888 new</i>	Blk oak	16 N 28° E	37				
8	W. 1/4 Sec. cor. Identified								
<b>SUBDIVISION CORNERS.</b>									
1	Center 1/4 Sec. cor.								
2	North 1/4-1/4s N. W. qr.								
3	East 1/4-1/4s N. W. qr.								
4	South 1/4-1/4s N. W. qr.								
5	West 1/4-1/4s N. W. qr.								
6	Center 1/4-1/4s N. W. qr.								
7	North 1/4-1/4s N. E. qr.								
8	East 1/4-1/4s N. E. qr.								
9	South 1/4-1/4s N. E. qr.								
10	Center 1/4-1/4s N. E. qr.								
11	East 1/4-1/4s S. E. qr.								
12	South 1/4-1/4s S. E. qr.								
13	West 1/4-1/4s S. E. qr.								
14	Center 1/4-1/4s S. E. qr.								
15	South 1/4-1/4s S. W. qr.								
16	West 1/4-1/4s S. W. qr.								
17	Center 1/4-1/4s S. W. qr.								

NAMES OF SWORN ASSISTANTS.

CHAINMEN.

FLAGMEN.

AXMEN.

J. Mc Glynan  
B. Johnson

MINUTES.

Starting at the Identified North East corner of sections 24 2-16-R-7-E and Run south at 43° 9'-V. 40 chains & 9 1/2 links to the Established Quarter Post on East side of said section then South at 50° 2'-V. 40 chains & 9 1/2 links to the Established South East corner of said section. said corner being established by running East from the Identified Quarter Post on south side of said section 40 chains (2 1/2 links) set Stone a corner

state of Wisconsin }  
County line I m. l. Smith county surveyor of Adams County do hereby certify that I have this day surveyed the line in of Highway on East side of section 24 Town 16-R-7-E, New Chester, the distance and variations being marked on Plat. Likewise the amount of encroachment in feet are marked opposite each stake, each stake is marked with the letter S & except round Post which is marked 1/4 S. The work was proven & is correct.

D. Mc Glynan & B. Johnson sworn chainmen. Dated this 18 day of June 1880  
M. l. Smith County Surveyor

The Bearings shown above were made by me (on this same work) in April 16th 1888

M. l. Smith County Surveyor

M1524160700002