

CERTIFICATE OF SURVEY.

STATE OF WISCONSIN, }
ADAMS COUNTY, } ss.

Wm. C. Smith Surveyor, in and for the County and State aforesaid, do hereby certify that I have surveyed and subdivided Section 5 Township 17 North of Range 6 East of 4th Principal Meridian, as represented by the courses and distances on the following plat, and annexed field-notes of survey:

Established the center of the section at the point of intersection of *straight* quarter lines.
Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.
Established all lost corners at proportionate distances between known corners, according to original field-notes of the Government survey:



Plat of Section 5, Township 17 North, Range 6 East of 4th Principal Meridian. Scale, 80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian _____ East.
Surveyed and subdivided this 7 day of April A. D. 1914, in accordance with the State Laws and Instructions of the Commissioner of the General Land Office, and recorded on pages _____ of Register in the County Surveyor's office.
WITNESS my hand this 7th day of April A. D. 1914.
Wm. C. Smith County Surveyor.

The above work was done at the request of Mrs. H. C. Fuller

MIS05170600013

DESCRIPTION of Section, Quarter Section and Quarter quarter Section Corners of Section
Township _____ North, Range _____ East of _____ Principal Meridian.

N. B.—The variation of needle adopted in establishing corners is _____

No.	Government Corners.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.
1	N. W. Sec. cor. Indentified								
2	N. E. Sec. cor. Indentified								
3	S. E. Sec. cor. Indentified								
4	S. W. Sec. cor. Indentified								
5	N. 1/4 Sec. cor. Indentified								
6	E. 1/4 Sec. cor. Indentified								
7	S. 1/4 Sec. cor. Indentified								
8	W. 1/4 Sec. cor. Indentified								
No. SUBDIVISION CORNERS.									
1	Center 1/4 Sec. cor.								
2	North 1/4-1/8 N. W. qr.								
3	East 1/4-1/8 N. W. qr.								
4	South 1/4-1/8 N. W. qr.								
5	West 1/4-1/8 N. W. qr.								
6	Center 1/4-1/8 N. W. qr.								
7	North 1/4-1/8 N. E. qr.								
8	East 1/4-1/8 N. E. qr.								
9	South 1/4-1/8 N. E. qr.								
10	Center 1/4-1/8 N. E. qr.								
11	East 1/4-1/8 S. E. qr.								
12	South 1/4-1/8 S. E. qr.								
13	West 1/4-1/8 S. E. qr.								
14	Center 1/4-1/8 S. E. qr.								
15	South 1/4-1/8 S. W. qr.								
16	West 1/4-1/8 S. W. qr.								
17	Center 1/4-1/8 S. W. qr.								

NAMES OF SWORN ASSISTANTS.

CHAINMEN.	FLAGMEN.	AXMEN.
<i>Wm. S. Smith</i> <i>Leon W. Parker</i>		

MINUTES.

Description of a tract of land on section 5-T-17-R-6-E known as the Barn lot commencing 6 chains 4.58 links east of the 1/4 Post on the west side of said section 5, and running thence North at 2nd degree East 14 chains to the south side of the Mill Pond, thence South 65th Degree East along the north edge of said Pond 168 links to Post. Thence South 183 links to Post. Thence West 46 links to Post. Thence South 140 links to Post. Thence West on the quarter line 109 links to Post a place of beginning. an Iron Post is set at every corner. The southwest corner of said lot, is South 17th Degree East, 46 feet from the southeast Post of the windmill.

Wm. S. Smith county surveyor

M505170600013