

DESCRIPTION of Section, Quarter Section and Quarter quarter Section Corners of Section

Township North, Range East of Principal Meridian.

N. B. - The variation of needle adopted in establishing corners is

No.	Government Corners.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.
1	N. W. Sec. cor. Identified								
2	N. E. Sec. cor. Identified								
3	S. E. Sec. cor. Identified	<i>new</i>	<i>Blk oak</i>	<i>20 N-17 1/2 W</i>	<i>148 1/2</i>				
4	S. W. Sec. cor. Identified								
5	N. 1/4 Sec. cor. Identified								
6	E. 1/4 Sec. cor. Identified								
7	S. 1/4 Sec. cor. Identified								
8	W. 1/4 Sec. cor. Identified								
SUBDIVISION CORNERS.									
1	Center 1/4 Sec. cor.								
2	North 1/4-1/4s N. W. qr.								
3	East 1/4-1/4s N. W. qr.								
4	South 1/4-1/4s N. W. qr.								
5	West 1/4-1/4s N. W. qr.								
6	Center 1/4-1/4s N. W. qr.								
7	North 1/4-1/4s N. E. qr.								
8	East 1/4-1/4s N. E. qr.								
9	South 1/4-1/4s N. E. qr.								
10	Center 1/4-1/4s N. E. qr.								
11	East 1/4-1/4s S. E. qr.								
12	South 1/4-1/4s S. E. qr.								
13	West 1/4-1/4s S. E. qr.								
14	Center 1/4-1/4s S. E. qr.								
15	South 1/4-1/4s S. W. qr.								
16	West 1/4-1/4s S. W. qr.								
17	Center 1/4-1/4s S. W. qr.								

NAMES OF SWORN ASSISTANTS.

CHAINMEN.	FLAGMEN.	AXMEN.
<i>Ben Sullivan</i> <i>O Anderson</i>		

MINUTES.

Starting at the Identified Stone at the N E corner of section 20 218-R-5-E and run South and North west in center of old Highway to a Post 17 chains and 57 links in center of Highway and at east of new Highway (for new Bridge) then South 19 degree East 3 chains & 90 1/2 links to Post in center of new Highway on south side of creek. Then South 3 degree East 3 chains & 88 links to Post in center of old Highway and to intersect same at Bridge across old slough. Made one new Bearing at North East corner of section as shown above.

M. L. Smith County Surveyor

MIS 20180500001

CERTIFICATE OF SURVEY.

STATE OF WISCONSIN,
ADAMS COUNTY, WIS.

ss. *M. H. Smith*

Surveyor, in and for the County and State aforesaid, do

hereby certify that I have surveyed and subdivided Section 20 Township 18 North of Range 5 East of 4th Principal Meridian, as represented by the courses and distances on the following plat, and annexed field-notes of survey:

Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.
Established all lost corners at proportionate distances between known corners, according to original field-notes of the Government survey:



Plat of Section 20, Township 18 North, Range 5 East of 4th Principal Meridian. Scale 80 chains to 6.3 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian East.
Surveyed and subdivided Adams Co. Wis. True Meridian East A. D. 1910 in accordance with the State Laws and Instructions of the Commissioner of the General Land Office, and recorded on pages 119 of Register in the County Surveyor's office.

WITNESS my hand this 1st day of Aug A. D. 1910
WITNESS my hand this 1st day of Aug A. D. 1910
M. H. Smith Surveyor.

The above work was done by the request of and for the Town Board of the Town of Strong Prairie Ben Sullivan & O. Anderson supervisors.

MIS2018050001