

17/183

No. 310.

CERTIFICATE OF SURVEY.

STATE OF WISCONSIN, } ss: M. C. Smith Surveyor, in and for the County and State aforesaid, do
ADAMS COUNTY. }

hereby certify that I have surveyed and subdivided Section 33 Township 18 North of Range 6 East of 11th Principal Meridian, as represented by the courses and distances on the following plat, and annexed field-notes of survey:

Established the center of the section at the point of intersection of straight quarter lines.

Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.

Established all lost corners at proportionate distances between known corners, according to original field-notes of the Government survey:



Plat of Section 33, Township 18 North, Range 6 East of 11th Principal Meridian. Scale, 80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian _____ East.

Surveyed and subdivided this 7th day of November A. D. 1913, in accordance with the State Laws and Instructions of

the Commissioner of the General Land Office, and recorded on pages _____ of Register in the County Surveyor's office.

WITNESS my hand this 7th day of November A. D. 1913.

M. C. Smith County Surveyor.

The above work was done at the request of Thomas Deemar

*Oked
J. E. B.*

*At or to
near
section
Adams
the 12th
south
of the
11th*

MIS 33180500001

DESCRIPTION of Section, Quarter Section and Quarter quarter Section Corners of Section

183

Township _____ North, Range _____ East of _____ Principal Meridian.

N. B.—The variation of needle adopted in establishing corners is _____

late aforesaid, do
last of 4th

quarter section
ament survey:

No.	Government Corners.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.
1	N. W. Sec. cor. Identified								
2	N. E. Sec. cor. Identified								
3	S. E. Sec. cor. Identified								
4	S. W. Sec. cor. Identified								
5	N. $\frac{1}{4}$ Sec. cor. Identified								
6	E. $\frac{1}{4}$ Sec. cor. Identified								
7	S. $\frac{1}{4}$ Sec. cor. Identified								
8	W. $\frac{1}{4}$ Sec. cor. Identified								
SUBDIVISION CORNERS.									
1	Center $\frac{1}{4}$ Sec. cor.								
2	North $\frac{1}{4}$ - $\frac{1}{4}$ s N. W. qr.								
3	East $\frac{1}{4}$ - $\frac{1}{4}$ s N. W. qr.								
4	South $\frac{1}{4}$ - $\frac{1}{4}$ s N. W. qr.								
5	West $\frac{1}{4}$ - $\frac{1}{4}$ s N. W. qr.								
6	Center $\frac{1}{4}$ - $\frac{1}{4}$ s N. W. qr.								
7	North $\frac{1}{4}$ - $\frac{1}{4}$ s N. E. qr.								
8	East $\frac{1}{4}$ - $\frac{1}{4}$ s N. E. qr.								
9	South $\frac{1}{4}$ - $\frac{1}{4}$ s N. E. qr.								
10	Center $\frac{1}{4}$ - $\frac{1}{4}$ s N. E. qr.								
11	East $\frac{1}{4}$ - $\frac{1}{4}$ s S. E. qr.								
12	South $\frac{1}{4}$ - $\frac{1}{4}$ s S. E. qr.								
13	West $\frac{1}{4}$ - $\frac{1}{4}$ s S. E. qr.								
14	Center $\frac{1}{4}$ - $\frac{1}{4}$ s S. E. qr.								
15	South $\frac{1}{4}$ - $\frac{1}{4}$ s S. W. qr.								
16	West $\frac{1}{4}$ - $\frac{1}{4}$ s S. W. qr.								
17	Center $\frac{1}{4}$ - $\frac{1}{4}$ s S. W. qr.								

NAMES OF SWORN ASSISTANTS.

CHAINMEN.

FLAGMEN.

AXMEN.

*Alb Dunbar
J. Eblin*

80 chains to 6

Instructions of

Surveyor.

Dunbar

MINUTES.

*Starting at the Identified N E corner of Section 33-2-18-R5-E and
ran west at 7 D-V 97 chains & 42 links to the NW corner of said
section said corner was established by running 40 chains North from the
Identified Quarter Post on the west side of the section. Then striking at
the established Quarter Post on the N side of the section at bridge and ran
south 80 chains & 18 links to the Identified Quarter Post on the south side
of the section. set Posts every 80 Rods Then East from Post at center
of the section on the E & W Quarter line. 20 chains & set Post*

W. G. Smith County Surveyor

MIS33180500001