

CERTIFICATE OF SURVEY.

STATE OF WISCONSIN,
ADAMS COUNTY.

I, M. L. Smith Deputy Surveyor, in and for the County and State aforesaid, do

hereby certify that I have surveyed and subdivided Section 31 Township 20 North of Range 6 East of 4 Principal Meridian, as represented by the courses and distances on the following plat, and annexed field-notes of survey:

Established the center of the section at the point of intersection of straight quarter lines.
Established all quarter-quarter corners upon the section boundary at proportional distances between known section and quarter section corners, according to the original field-notes of the Government survey.
Established all lost corners at proportionate distances between known corners, according to original field-notes of the Government survey:



Plat of Section 31 Township 20 North, Range 6 East of 4 Principal Meridian. Scale, 80 chains to 6 inches. The figures in red ink are the lengths of the lines as stated in the field-notes of the Government survey.

Declination of the Magnetic Meridian from the True Meridian _____ East.

Surveyed and subdivided April 7th

A. D. 1907, in accordance with the State Laws and Instructions of

the Commissioner of the General Land Office, and recorded on pages _____ of Register in the County Surveyor's office.

WITNESS my hand this 7th day of April A. D. 1907.

M. L. Smith Deputy Surveyor.

No.	SUBDI
1	Center
2	North
3	East
4	South
5	West
6	Center
7	North
8	East
9	South
10	Center
11	East
12	South
13	West
14	Center
15	South
16	West
17	Center

*Frank Adin
John Boy*

*Of the sec
starting at
line hence
section 40.2
line to "iden
31, made me
4 Post on
hence vic
section, 2*

MIS31200600001

DESCRIPTION of Section, Quarter Section and Quarter quarter Section Corners of Section 19

Township North, Range East of Principal Meridian.

N. B. - The variation of needle adopted in establishing corners is

Government Corners.		Bearing Trees.	In. dia.	Courses they bear.	Links Distant.	Bearing Trees.	In. dia.	Courses they bear.	Links Distant.
No. 1	N. W. Sec. cor. Identified	New	Blk Pine	12 S. 31. E.	38 3/4				
No. 2	N. E. Sec. cor. Identified								
No. 3	S. E. Sec. cor. Identified								
No. 4	S. W. Sec. cor. Identified								
No. 5	N. 1/4 Sec. cor. Identified	New	Blk Pine	9 S. 53. W.	18				
No. 6	E. 1/4 Sec. cor. Identified								
No. 7	S. 1/4 Sec. cor. Identified								
No. 8	W. 1/4 Sec. cor. Identified								
SUBDIVISION CORNERS.									
No. 1	Center 1/4 Sec. cor.								
No. 2	North 1/4-1/4s N. W. qr.								
No. 3	East 1/4-1/4s N. W. qr.								
No. 4	South 1/4-1/4s N. W. qr.								
No. 5	West 1/4-1/4s N. W. qr.								
No. 6	Center 1/4-1/4s N. W. qr.								
No. 7	North 1/4-1/4s N. E. qr.								
No. 8	East 1/4-1/4s N. E. qr.								
No. 9	South 1/4-1/4s N. E. qr.								
No. 10	Center 1/4-1/4s N. E. qr.								
No. 11	East 1/4-1/4s S. E. qr.								
No. 12	South 1/4-1/4s S. E. qr.								
No. 13	West 1/4-1/4s S. E. qr.								
No. 14	Center 1/4-1/4s S. E. qr.								
No. 15	South 1/4-1/4s S. W. qr.								
No. 16	West 1/4-1/4s S. W. qr.								
No. 17	Center 1/4-1/4s S. W. qr.								

NAMES OF SWORN ASSISTANTS.

CHAINMEN.	FLAGMEN.	AXMEN.
Frank Adams John Hoyt Jr		

MINUTES.

Of the survey of the NW 1/4 of section 31 town 20-R-6-E
 starting at the "identified" 1/4 Post on west side of said section on town
 line thence North at 5.30 V to "identified" North west corner of said
 section 40-22. set Post & made one New Bearing. Then East on section
 line to "identified" 1/4 Post at the North corner of the NW 1/4 NW 1/4 of said
 section. made one New Bearing. thence South at 5.00 V to the "identified"
 1/4 Post on south side of section. Distance 8000 set Post at center
 thence west from center Post at 5.00 V to 1/4 Post on west side of
 section. Distance 3888

M. C. Smith Deputy Co Surveyor

MIS 31200600001

the
 E
 V
 the
 5.00 V
 E
 NW
 section
 the from
 Post
 of NW 1/4
 NW 1/4
 you