**SECTION** 

TYPE OF MONUMENT:

## **DOCUME** ADAMS COUNTY

COUNTY CORNER NO: 20

ROMPORTOL ID: 41506012000

## PUBLIC LAND SURVEY MONUMENT RECORD


ADAMS COUNTY COORDINATES, NAD 83 (2007) N. **161966.811** E. 557748.707 DATUM **ELEVATION-**09/20/2017 FIELD WORK DATE:

## BASIS FOR MONUMENT LOCATION

1972 - PLS 981 SET A 30" HARRISON MONUMENT AT THE CORNER LOCATION AND TIED OUT.

1999 - 2281 HARRISON MONUMENT WAS RE-SET AFTER COMPLETION OF COUNTY HIGHWAY B RECONSTRUCTION PROJECT. LOCATION IS BASED ON THE EXISTING MONUMENT FOUND BEFORE CONSTRUCTION BEGAN. CORNER WAS RE-TIED.

2017 - PLS 2994 FOUND A HARRISON MONUMENT 6" BELOW THE ROAD SURFACE, 3 TIES AND 1 PROPERTY IRON USED AS A TIE. THE MONUMENT AGREES WITH THE EXISTING TIES AND PROPERTY IRON. ACCEPTED THE HARRISON MONUMENT AS THE CORNER LOCATION. SET 1 NEW TIE AND RE-MEASURED TO THE TIES AND PROPERTY IRON.



LOCATION (INDICATE CORNER BY "X")



DATA SHOWN HERE ON THIS TIE SHEET IS CORRECT AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF.

PROFESSIONAL LAND SURVEYOR

11-15-17 DATE

- TIE SKETCH



- 3/4" x 18" IRON REBAR SET, 1.50#/FT O 1-1/4" O.D. IRON PIPE FOUND
- ⊕ 3/4" IRON ROD FOUND
- HARRISON FOUND
- → VINYL "T" POST

PINE PLANTATION FIELD 52.45 N 89°53'32" E 32.96 TREE LINE

ADAMS COUNTY	CORNER NO
Survey Monument Record	SECTION
TYPE OF MONUMENT: 30" HARRISON	TOWN
STATE PLANE COORDINATES: N	range 6
<u>E</u>	
ELEVATION — M.S.L. DATUM:	
THETA ANGLE:	
TAGE	
BASIS FOR MONUMENT LOCATION	
(Use reverse side if necessary)	
Show info such as: History of corner, with reference to Vol. and pg, dates, surveyor; exact description of monument replaced; if location computed, by taped or EDM traverse; landowner remarks, etc.	LOCATION (Indicated by 'X') SEAL:
Set 30" Harrison monument on May 17, 1972	
Sam T. Mullen R.L.S. 981	
CORNER O.K. 4-23-76 PN-55	
MAINTENÁNCE RECORD	
Date Init. Remarks	
12-30-81 SK-RW CORNER O.K.	
1-16-86 GR-55 "1	
1-31-91 KZ-56 ALL OK 11-22-95 55 / GONG O ANDLESIE	·
SEE ATTACHED SHEET GROUDLEN 12/21/99	CERTIFIED CORRECT:
2-6-01 JG DK SEE ATTACHED SHEET	Registered Land Surveyor
3-13-06 76-55 11 4	DATE:
TIE SKETCH  (Show at least four ties)  R.R. SPIKE  (Norway PINE 87	RR SPIKE
NAIL A.B. SPIKE TO POST	AR SPIKE IN PINE/- 10" white of
POST	
-x-x-x-x	
6	
33.00'	Ol"I.P. R.K. Sayler
33.85	T NAIL IN
	T NAIL IN POST
V	
, φ , σ , σ , σ , σ , σ , σ , σ , σ , σ	
\(\frac{1}{2}\)	
` úl	

₩

ADAMS COUNTY U.S. PUBLIC LAND	SURVEY	CORNER #20
MONUMENT LOCATION RECORD		SECTION1
MONOMENT ECCATION RECORD	☐ FOUND ☐ SET	TOWNSHIP 15 NORTH RANGE FAST
	X RE-SET	SECTION 1
CORNER IDENTITY: EAST QUATER CONER	☐ RE-TIED	
STATE PLANE COORDINATE: N:	{	
E:		
ZONE:		
DATUM:		
THETA ANGLE:		
WEATHER: SUNNY/COLD TEMPERATURE: 48° F	1	
DATE OF SURVEY: 12/1/99	i	
SURVEY PARTY: MARK HINTZ / BOB LASKY	•	LOCATION
BASIS FOR MONUMENT LOCATION.  (DESCRIBE METHOD OF SURVEY AND CORNER AUTHENTICATION)  HARRISON MONUMENT RESET AFTER COMPLETION OF COUNTY HIGHWAY B RECONSTRUCTION PROJECT. LOCATION IS BASED ON THE EXISTING MONUMENT FOUND BEFORE CONSTRUCTION BECAN.	del	SCOTT R GROHOLSKI (RLS #2281)
SHOW MINIMUM OF FOUR (4) HORIZON DESCRIBE ALL MONUMENTS FOUND OR TEMPERATURE OF 68° F.  LEGEND  O 1 1/4" IRON PIPE SET  HARISON MONUMENT SET  XX. EDGE OF BITUMINOUS  CENTER LINE  -X FENCE LINE  GRAVEL DRIVE  TELEPHONE PEDISTAL  O 1 1/4" IRON PIPE SET  A 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		