

ADAMS COUNTY

Survey Monument Record

TYPE OF MONUMENT: HARRISON STANDARD 30 inches

STATE PLANE COORDINATES: N \_\_\_\_\_

E \_\_\_\_\_

ELEVATION — M.S.L. DATUM: \_\_\_\_\_

THETA ANGLE: \_\_\_\_\_


FIELD BOOK: \_\_\_\_\_ PAGE \_\_\_\_\_

CORNER NO. 645 <sup>(64)</sup>

SECTION 20

TOWN 16

RANGE 6



LOCATION (Indicated by 'X')

SEAL:



BASIS FOR MONUMENT LOCATION

(Use reverse side if necessary)

Show info such as: History of corner, with reference to Vol. and pg, dates, surveyor; exact description of monument replaced; if location computed, by taped or EDM traverse; landowner remarks, etc.

Excavated with backhoe. Found 1 1/4" iron pipe 36" long, surrounded with four large sandstones. Replaced pipe with Harrison and replaced stones around it. Excavation witnessed by John Breene, adjacent landowner, who had recalled seeing the corner before.

(A.K. & Rod Knoll)

Everything in good shape 10/28/75 OM-SS

1 Gone 6-26-85 SS-GR

OK 1-30-90 GR

ALL OK 1-9-95 JG-BS

ALL OK, 2-16-00 JG-SS

1-GONE, 2-NEW, 2-25-05-JG

1-13-10 OK SS

CERTIFIED CORRECT:

*Anthony B. Kiedrowski*  
Registered Land Surveyor

DATE: April 22, 1975

TIE SKETCH

(Show at least four ties)

