## OS ADAMS COUNTY

COUNTY CORNER NO: 20

ROMPORTOL ID: 41905012000


## PUBLIC LAND SURVEY MONUMENT RECORD

**HARRISON** TYPE OF MONUMENT: ADAMS COUNTY COORDINATES, NAD 83 (2007) N. **284903.519** E. 525534.559 DATUM - -01/17/2018 FIELD WORK DATE:


## BASIS FOR MONUMENT LOCATION

1980 - PLS 1478 SET A HARRISON MONUMENT BY SINGLE PROPORTIONATE AND ON A LINE BETWEEN ADJACENT SECTION CORNERS. NO EVIDENCE OF ANY PREVIOUS MONUMENTATION WAS FOUND. NO RECORD OF ANY MONUMENTATION SUBSEQUENT TO THE ORIGINAL WAS FOUND. TIED OUT CORNER.

2018 - PLS 2994 FOUND A HARRISON MONUMENT FLUSH WITH THE GROUND SURFACE AND 4 WITNESS TREES. THE MONUMENT AGREES WITH THE EXISTING WITNESS TREES. ACCEPTED THE HARRISON MONUMENT AS THE CORNER LOCATION. SET 4 NEW TIES AND MEASURED TO THE TIES AND WITNESS TREES.



LOCATION (INDICATE CORNER BY "X")




DATA SHOWN HERE ON THIS TIE SHEET IS CORRECT AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF.

PROFESSIONAL LAND SURVEYOR

3-1-18

- TIE SKETCH





 3/4" x 18" IRON REBAR SET, 1.50#/FT HARRISON FOUND

VINYL "T" POST

WITNESS TREE FOUND

Government Land Corner Certificate	30
ADAMS County	CORNER NO.
TYPE OF MONUMENT: HARRISON STANDARD	SECTION
STATE PLANE COORDINATES: N	necket TOWN
E	RANGE 5
ELEVATION — M.S.L. DATUM:	
THETA ANGLE:	
DRAWN BY:	<b>5.</b>
	_
BASIS FOR MONUMENT LOCATION	
Show info such as: History of corner, with reference to Vol.	
and pg., dates, surveyor; exact description of monument replaced; if location computed, by taped or EDM traverse;	LOCATION
landowner remarks, etc. (Use reverse side if necessary)	(Indicated by 'X') SEAL:
Set monument single proportionate and on	GREGORY P. RHINEHART S-1478 Wisconsin Rapids Wis.
line between adjacent section corners.	WING CONSTILL
line between adjacent section corners.  No evidence of any previous monumentation	THE STATE OF THE S
found. No record of any monumentation	GREGORY P. RHINEHART
found. No record of any monumentation subsequent to the original was found.	S-1478 Wisconsin Rapids
	Wis.
	E A CONTRACTOR AND THE CONTRACTO
1. 1. 1. 1. 1.22/80 -6 11.	NO SURV
Ok 4-17-84 DK-SS	DATA SHOWN HERE ON
1 1000 No. 1203-35 No. 1818	CERTIFIED CORRECT:
OK 3-2-94 JG	Gregory P Rhine Past
OK, 2-12-98- JG	Registered Land Surveyor
DK, 12-30-02-56 ADD 1 TE 2-12-09 55	DATE: 1/30/80
TIE SKETCH PINE 3	
Show at least four ties, also fence lines, roads, topo, size	N state
and type of witness trees' and if off road - best way to arrive at corner.	6" BLACK DAK
	<i>{</i> ∕6 <i>}</i> /8/ <sup>3</sup>
Monument is located 600 feet south of dead end	
road.	n .
	(h)
TIME BY	40' ± ->
1798 8 38.6	•
ST STEAR OF THE	
	Solz" BLACK OAK
IO" BLACK DAY, (O) BT & D.N.D. SIGN	(0) 12 BLACK CAR
BT & DN.O.	
Sign i	
347	
۱ ۴	

## MAINTENANCE RECORD

DATE	BY WHOM	REMARKS
	·	A*
<u> </u>		