27 SECTION

OT RANGE ADAMS COUNTY C

PUBLIC LAND SURVEY MONUMENT RECORD

2-3/8" O.D. IRON PIPE TYPE OF MONUMENT: ADAMS COUNTY COORDINATES, NAD 83 (2007) N. 263963.710 E. 578004.113


- — — DATUM_ **ELEVATION-**05/14/2019

BASIS FOR MONUMENT LOCATION


FIELD WORK DATE:_

1983 - PLS 1551 SEARCHED AREA FOR ORIGINAL CORNER STAKE AND BEARING TREES, NOTHING WAS FOUND. CORNER WAS RESET PROPORTIONALLY ON A STRAIGHT LINE BETWEEN ADJACENT SECTION CORNERS. LOCATION USED FOR THIS CORNER IS WITH 2.5 FEET OF THE ORIGINAL DISTANCE.

2019 - PLS 2675 FOUND 2-3/8" O.D. IRON PIPE 12" ABOVE THE SWAMP SURFACE. DID NOT RECOVER ANY TIES OR WITNESSES. ACCEPTED 2-3/8" O.D. IRON PIPE AS THE CORNER LOCATION AND SET 4 NEW TIES.



(INDICATE CORNER BY "X")



DATA SHOWN HERE ON THIS TIE SHEET IS CORRECT AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF.

PROFESSIONAL LAND SURVEYOR


DATE

- TIE SKETCH



SWAMP

AllZ



SET 3/4" x 48" IRON REBAR, 1.50#/FT

FOUND 2-3/8" O.D. IRON PIPE MONUMENT

VINYL "T" POST

U.S. PUBLIC LAND SURVEY MONUMENT RECORD 98 CORNER NO. . ADAMS COUNTY 26 SECTION TYPE OF MONUMENT: 2" I.D. x 60" galvanized pipe 19N TOWN STATE PLANE COORDINATES: 7E **RANGE** ELEVATION - M.S.L. DATUM: THETA ANGLE: FIELD BOOK: Adams County 68 _ PAGE _ DRAWN BY: D. Riesop BASIS FOR MONUMENT LOCATION Show info such as: History of corner, with reference to Vol. and pg., dates, surveyor; exact description of monument replaced; if location computed, by taped or EDM traverse; landowner remarks, etc. (Use reverse side if necessary) (in conformance with Section A-E 502 of the LOCATION (Indicated by 'X') SEAL: DAVID C. RIESOP S-1551 CAMBRIDGE, WISCONSIN Wisconsin Administrative Code) Searched area for original corner stake and bearing trees, nothing was found. Corner was reset proportionally on a straight line between adjacent section corners. Location used for this corner is within 2.5' feet of the original distance. DATA SHOWN HERE ON CERTIFIED CORRECT: Registered Land Surveyor DATE: 9/29/83 TIE SKETCH 6" WILLOW, NAIL IN S. SIDE Show at least four ties, also fence lines, roads, topo, size and type of witness trees' and if off road - best way to 5"ASH CLUMP, NAIL arrive at corner. IN S. SIDE 589°48'E MAINTENANCE RECORD Date Init. Remarks UNDER 6" POPLAR, -24-92 تاك MAIL IN S. SIDE SCALE 8 1"= 100" 6" POPLAR, NAIL IN W. SIDE لمحصا HOLBACK