16

OT RANGE ADAMS COUNTY COUNTY CORNER NO: 86

ROMPORTOL ID: 41607210020

PUBLIC LAND SURVEY MONUMENT RECORD


HARRISON (BROKEN-TOP) TYPE OF MONUMENT: ADAMS COUNTY COORDINATES, NAD 83 (2007) N. 175309.777 E. 570675.635

ELEVATION- - - DATUM 10/01/2020 FIELD WORK DATE:

BASIS FOR MONUMENT LOCATION

1979 - PLS 1478 SET MONUMENT EQUIDISTANT AND ON LINE BETWEEN ADJACENT SECTION CORNERS. NO RECORD OF ANY MONUMENTATION SUBSEQUENT TO THE ORIGINAL WAS FOUND. NO EXCAVATION WAS MADE DUE TO CUT IN ROADWAY AT THIS CORNER.

2020 - PLS 2675 FOUND HARRISON (BROKEN-TOP) 6"± BELOW THE ROAD SURFACE AND 1 TIE. THE MONUMENT AGREES WITH THE TIE. ACCEPTED THE HARRISON (BROKEN-TOP) AS THE CORNER LOCATION. SET 3 NEW TIES AND MEASURED TO THE **EXISTING TIE.**



(INDICATE CORNER BY "X")



DATA SHOWN HERE ON THIS TIE SHEET IS CORRECT AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF.

PROFESSIONAL LAND SURVEYOR

11/3/2020 DATE

-TIE SKETCH

NOTE: THE CORNER LANDS ON THE CENTERLINE OF EMBER AVE.



MIXED WOODS AVE. **EMBER** 04'34"W S11° MIXED WOODS O

- SET 3/4" x 18" IRON REBAR, 1.50#/FT
- FOUND 1-1/4" O.D. IRON PIPE
- FOUND HARRISON (BROKEN-TOP) MONUMENT
- VINYL "T" POST

Government Land Corner Certificate CORNER NO. Adams County 28 SECTION Harrison TYPE OF MONUMENT: _ 16 TOWN STATE PLANE COORDINATES: N RANGE ELEVATION — M.S.L. DATUM: THETA ANGLE: _ FIELD BOOK: _ PAGE . DRAWN BY: N.J. BASIS FOR MONUMENT LOCATION Show info such as: History of corner, with reference to Vol. and pg., dates, surveyor; exact description of monument replaced; if location computed, by taped or EDM traverse; LOCATION landowner remarks, etc. (Use reverse side if necessary) (Indicated by 'X') GREGORY P. RHINEHART S-1478 Wisconsin Rapids Wis. SEAL: Set monument equidistant and on line between adjacent section corners. No record of any monumentation subsequent to the original was found. No excavation was made due to cut in roadway at this corner. DATA SHOWN HERE ON CERTIFIED CORRECT: DATE: TIE SKETCH FIELD Show at least four ties, also fence lines, roads, topo, size and type of witness trees' and if off road - best way to arrive at corner. 5" BLK 8± 14" BLK BT. EMBER AVE. IX24" I.P. SET PLANTATION OPPOSITE FENCE

MAINTENANCE RECORD

DATE	BY WHOM		REMARKS		
3.55-85	Phinehart -	Sorensen	O.K.		
12-9-86	"	**/			
17-26-91	K2-612		Ц		
12-6-96	55				
1-02-02	ML		+1		
6-11-07	ML JG		ં ા		
0-11-07	MS		OK		